



NOTE:

AIR PRESSURE: 30-100 P.S.I.
 PRESSURE RATIO: 1:65
 MAXIMUM OIL PRESSURE: 6500 P.S.I.
 NITRILE SEALS

R48265-01	OIL INTENSIFIER	40#	"HYDRONIC" #F826-65-N-W-SAE6/8
PART NO.	PART DESCRIPTION	EST. WT.	MATERIAL DESCRIPTION
McNEIL & NRM INC. NRM		PART NO. LIST	
OIL INTENSIFIER UNIT		52/385 AUTOLOK CT-4	
DECIMAL TOLERANCES (UNLESS OTHERWISE NOTED)		SCALE FULL	
UNIFORM DIMENSIONS: UNIFORM DIMENSIONS X = ± .030 UP TO 18" = ± 1/16" Y = ± .015 OVER 18" TO 36" = ± 1/8" Z = ± .005 OVER 36" = ± 3/16" ANGLES = ± 1/4° ROUNDED ANGLES = ± 2°		DWN. BY: D.Z. CHK. BY: G.R. DATE: 02/20/02 DES: 5-44720 SHEET: 4 OF 1	
ALL DIMENSIONS IN INCHES (UNLESS OTHERWISE NOTED) DO NOT SCALE DIMENSIONS THIS DRAWING CREATED ELECTRONICALLY DO NOT REUSE MANUALLY BRIDGE SHOP ENTER 208 TO 218 X 40' OR 208 TO 218 R.		SHEET 1 OF 1	

REV.	DATE	DESCRIPTION	DATE	BY	APPV.
		ASTM A36 STEEL MINIMUM CARBON = .16%			