

A1

A2 MATERIALS OF CONSTRUCTION
1- TIN PLATED END CAPS WITH CORROSION RESISTANT O-RING INSERTS.
2- TIN PLATED CENTERTUBES.
3- CARBON IMPREGNATED MEDIA.
4- BUNA-N O-RINGS.
5- CARTRIDGE RATED FOR 100 PSI COLLAPSE
6- CARTRIDGE RATED FOR 250° F MAX.
A3 7- PLEATED MICROGLASS MEDIA WITH CARBON MEDIA SUPPORTED ON BOTH SIDES BY EPOXY COATED SCREEN.
8- BETA 41= 200

REV	DESCRIPTION	BY	DATE	APP
A	1-DESIGN UPDATE, WAS URETHANE END CAPS 2-NOTE #1 WAS MOLDED URETHANE ENDS 3-NOTE #7 WAS "WITH LAYER OF CARBON MEDIA" ECN: 05-201500128	ROC	11/5/15	LTH

THE INFORMATION AND DATA CONTAINED HEREIN CONFORMS TO ASME Y14.5-M 1994

DRAWING STATUS: **PRODUCTION**

THIS DOCUMENT CONTAINS PROPRIETARY INFORMATION AND SUCH INFORMATION MAY NOT BE DISCLOSED TO OTHERS OR USED FOR ANY PURPOSE WITHOUT WRITTEN PERMISSION FROM THE HILLIARD CORP.
©COPYRIGHT THE HILLIARD CORPORATION, ALL RIGHTS RESERVED

MAKE FROM

UNLESS OTHERWISE SPECIFIED: MACHINE 125 MICROINCHES
UNLESS OTHERWISE SPECIFIED: BREAK CORNERS .015 MAX
UNLESS OTHERWISE SPECIFIED: FRACTIONAL ± 1/16; DECIMAL .XX ± .01, .XXX ± .005; ANGLES ± 1°

THE HILLIARD CORPORATION
100 WEST FOURTH STREET
ELMIRA, NEW YORK 14902

DIMENSIONS ARE IN INCHES [ ] DIMENSIONS IN MM

	BY:	DATE:
DRAWN	ROC	05/04/11
CHECKED	LTH	05/05/11
APPROVED	LTH	05/05/11
SIMILAR TO:		
SCALE: 1/2		

TITLE: DATA SHEET PH739-05-CGJ

SHEET 1 OF 1

DD-700-413 C