


AIR AND GAS FILTERS

70600

Aluminium wall-mounting gas filter with galvanised steel cover; Viledon P15/500S filter element approved to DIN EN779, synthetic filter cage; NBR cover O-ring. Suitable for manufactured gas, natural gas, liquefied petroleum gas (LPG), non-aggressive gas and air. Filtration rating 50 µm. PN 0.5. Operating temperature range: -10÷80°C.



Type	Part Number	Connection	Q.ty/Box	Box/ Carton
70609	007.0030.100	1/2"	36	36
70608	007.0031.100	3/4"	36	36

Dimensions on page 15

70600/1B

Aluminium gas filter; Viledon P15/500S filter element approved to DIN EN779, synthetic filter cage; NBR cover O-ring. Suitable for manufactured gas, natural gas, liquefied petroleum gas (LPG), non-aggressive gas and air. Filtration rating 50 µm. PN 1. Operating temperature range: -20÷80°C.



Type	Part Number	Connection	Q.ty/Box	Box/ Carton
70611/1B	007.0040.100	1/2"	1	1
70612/1B	007.0041.100	3/4"	1	1
70602/1B	007.0042.100	1"	1	1
70604/1B	007.0043.100	1.1/4"	1	1
70603/1B	007.0044.100	1.1/2"	1	1
70631/1B	007.0045.100	2"	1	1

Dimensions on page 15

70600/6B

Aluminium gas filter; filter element composed of two Viledon P15/500S panels approved to DIN EN779, synthetic filter cage with penetration-resistant steel reinforcement; NBR cover O-ring. With two tapping points. Suitable for manufactured gas, natural gas, liquefied petroleum gas (LPG), non-aggressive gas and air. PN 6 with 2 tapping points. Filtration rating 50 µm. Operating temperature range: -20÷80°C.



Type	Part Number	Connection	Q.ty/Box	Box/ Carton
70611/6B	007.0060.000	1/2"	1	1
70612/6B	007.0061.000	3/4"	1	1
70602/6B	007.0062.000	1"	1	1
70604/6B	007.0063.000	1.1/4"	1	1
70603/6B	007.0064.000	1.1/2"	1	1
70631/6B	007.0065.000	2"	1	1

Dimensions on page 15